

GT600

Intruder Alarm Control Panel

'Probably the easiest to use graded control unit available'

Main Features

Zones: 8 Fully Programmable
expandable to 40

Number of User Codes: 31

G Tag Proximity Fob Compatible

Areas: 3

Part Sets: 2

Silent Part Set Option

English Text Display

Time & Date

Zone Descriptions

User Names

Event Log: 500 Events

Remote Communication Capability:

On Board Modem*

On Board Voice Communicator

On Board Digital Communicator

Blank End Station (Hide-away):
Polycarbonate - PD662 Grade 2

*The option to connect a Modem allows us to access the system remotely for maintenance checks, diagnostics, event log reading (with the ability to print off hard copies) and to make changes to the programme settings without the cost of a site visit.



CONTOUR
Remote Key Pad

G Tag
Proximity Fob
(Optional)



Built to Perform

Gardtec produce well designed Professional Grade Intruder Alarm Panels designed to be permanently connected to the mains supply. They are designed to withstand 'voltage spikes' or 'transients' on the mains supply caused by other mains operated equipment.

Poorly designed panels can suffer with false alarms associated with such transients etc. with add-on filters (often described as surge protectors) fitted to overcome these problems.



OWL SECURITY SERVICES LTD
OWL ALARMS

Tel 01443 224695

Fax 01443 238600

enquiries@owlsecurity.co.uk

